

Information:

Drawer: Accounts Payable - Invoices

Vendor Number: 1504171

Vendor Name: Al Warren Oil Company, Inc.

Invoice Number: W1297934

Invoice Date: 03/19/20

PO Number: B0365251

Check Number: 0266562

Check Amount: \$ 2,813.97

Check Date: 04/14/2020

Department ID: 00701

Reviewer Name:

Voucher Number: V0608911

Redaction Type: None

Document Type: AP Invoice-3 Way/Pre-Approved

Document Below

From: QRI@alwarrenoil.com
Sent: Thu Mar 19 14:35:04 CDT 2020
To: invoicing@cod.edu
CC:
Subject: Al Warren Oil Invoice

Attached is invoice #W1297934. Meter ticket(s) are also attached. We thank you for your business!

CONFIDENTIALITY NOTICE: This email message is intended only for the person or entity to which it is addressed and may contain confidential and/or privileged material. If you received this electronic transmission in error, please be aware that any unauthorized review; copying, use, disclosure or distribution of this information is prohibited. If you are not the intended recipient, please contact the sender by reply email, then delete the original message, including any attachments, and destroy all copies.

AL WARREN OIL CO., INC.

Since 1948

Specialized Petroleum Marketers

Sold To: COLLEGE OF DUPAGE COMMUNITY SCHOOL DISTRICT 502
ACCTS PAYABLE
425 FAWELL BLVD
GLEN ELLYN, IL 60137

Invoice #: W1297934
Invoice Total: \$503.85
Invoice Date: 03/19/20
Customer #: C08363

Ship To: COLLEGE OF DUPAGE COMMUNITY SCHOOL DISTRICT 502
425 FAWELL BLDV
GLEN ELLYN, IL 60137 DU PAGE

SO #: D0000589002
Purchase Order #: 352822

Job #	Delivery Date	Quantity	Description	Unit Price / Rate	Job Total
1528483	03/17/20	300.0000	ULSD ON HIGHWAY UNDYED FUEL	1.2135	\$364.05
				Document # 521-83	
				State M.F. Tax	136.50
				IL U.S.T.	0.90
				IL E.I.F.	2.40
				Winter Blend	
				Load Total:	\$503.85

15-ppm sulfur (maximum) Undyed Ultra-Low Sulfur Diesel Fuel For use in all diesel vehicles and engines.

Order taken by Corporate office.
Al Warren Oil Company, Inc., 1646 Summer St., Hammond, IN 46320

Delivery Location Total: \$503.85

INVOICE REVIEWED
OKAY TO PAY
KATHY STRIPLIN 03/20/20
ELECTRONIC PAYMENT PREFERRED

ACH/WIRE INSTRUCTIONS:

Fifth Third Bank
ABA: 071923909
Account: 1900002976
Beneficiary: AL Warren Oil Company Inc.
Email Remittance: awocbilling@alwarrenoil.com

REMIT:

AL Warren Oil Company Inc.
P.O. Box 2279
Hammond, IN 46323


INVOICE

TOTAL: \$503.85



1646 SUMMER STREET, HAMMOND, IN 46320
WWW.ALWARRENOIL.COM
AWOCBILLING@ALWARRENOIL.COM
Phone: 219.228.5050 Fax: 219.852.6010





WINTER FUEL PROGRAM

Dear Valued Customer,

With winter approaching we wanted to take this opportunity to notify you of our program for this upcoming season.

We will begin our winter additive blending process for all Diesel fuels on November 6th. We will cease biodiesel blending for above-ground tank deliveries (unless otherwise requested) and all direct-to-unit fills on December 2nd and proceed with distributing Ultra-Low Sulfur Diesel #2 with winter additive.

Please be advised that diesel fuel at the refinery level may contain up to 5% biodiesel without disclosure. Al Warren Oil Company, Inc. will not increase the percentage of biodiesel unless requested by customer.

In the anticipated occurrences that temperatures will reach single-digit and sub-zero range, it is Al Warren Oil Company, Inc.'s intent (based on product availability) to implement the following blending procedure for Ultra-Low Sulfur Diesel #2 and Ultra-Low Sulfur Diesel #1 including winter additive:

Less than 5°F	Less than -5°F	Less than -15°F
90% #2 — 10% #1 blend	80% #2 — 20% #1 blend	50% #2 — 50% #1 blend


****Do not over treat fuel with additional additives! AWOC's winter blends are treated with the maximum allowed concentration of additives. Over additizing by end user could have negative effects!**

Orders for exact gallons of "straight" Ultra-low Sulfur Diesel #1 tank fills may be satisfied upon request

Please be advised that pricing for the above blends and Ultra-low Sulfur Diesel #1 are subject to market conditions and possible transportation fees

ORDER NOW

Please contact your sales representative or dispatch (800-327-8903) for any requests or questions.
We thank you for your business and look forward to continuing service for all your needs.



FLEET MAINTENANCE

Al Warren Oil has products to help you through the winter.

BEFORE WINTER STARTS

- Have all vehicles winterized beginning November 01.
- Drain fuel water separators. (Constantly monitor and maintain above and beyond scheduled PM inspections)
- Change fuel filters (use highest OEM accepted micron fuel filters. Example 10-15 micron fuel filters as opposed to 2-5 micron fuel filters)
- Inspect fuel tanks for condensation
- Always top fuel tanks prior to equipment shut down
- Constantly monitor fuel system for condensation and microbial contamination

-35 PREMIUM WINDSHIELD DEICER

- Extreme cold calls for extreme fluid. Use our Negative 35 Premium Windshield Deicer for the harsh winter ahead. Ensure clear vision for your fleet.

Chevron XLC Antifreeze/Coolant 50/50

Delo® XLC Antifreeze/Coolant is a non-nitrated extended life OAT (Organic Additive Technology) formulation for heavy or light duty vehicles and other equipment. Delo XLC is formulated with an aliphatic carboxylate corrosion inhibitor system available as a concentrate and a premix 50/50.

CUSTOMER BENEFITS

Delo XLC Antifreeze/Coolant products deliver value through:

- Long Service Life — Service life of 1,000,000 miles / 1,600,000 km / 15,000 hours
- Excellent Protection — Excellent protection against pitting, corrosion and erosion even on hard to protect metals like aluminum.
- Hardware Life — Maximum water pump life due to no silicate formula.
- Compatibility — Compatible with conventional antifreeze.

12 TO 72 HOURS BEFORE EXPECTED TEMPS OF ZERO DEGREES OR COLDER

- Treat saddle tanks with fuel deicer - 1 qt per 50 gallons of diesel fuel
- Before shutting engine down, idle engine for 10-15 minutes to circulate treated fuel thru the entire fuel system.
- First start, let engine idle for 30-45 minutes. This will allow warm fuel to return fuel tanks and vital engine components. Thus dissolving any wax or ice build up in fuel. If adequate warm up time is not done, heavy waxy fuel will load up fuel system and engine will shut down due to fuel starvation.

WHAT DOES DIESEL EXHAUST FLUID DO?

- Diesel Exhaust Fluid is sprayed into the diesel exhaust streams of diesel engines to lower the concentration of nitrogen oxide, NOx, in emissions.

WHY BLUEDEF DIESEL EXHAUST FLUID?

- Engineered for use in Selective Catalytic Reduction (SCR) systems on diesel engines, BlueDEF diesel exhaust fluid is comprised of a high-purity synthetic urea and deionized water mixture that improves emissions and fuel economy.

HOW DIESEL EXHAUST FLUID WORKS.

- When injected into the exhaust stream with a specialized dosing module, BlueDEF's water vaporizes, leaving ammonia molecules en route to the catalytic converter; once there, it converts NOx molecules into harmless nitrogen and water vapor—making for cleaner emissions. To ensure Selective Catalytic Reduction (SCR) performance, diesel exhaust fluids must adhere to the ISO 22241 Standards.

BE PROACTIVE

Utilize engine block heaters. / Park trucks inside when possible. / Drain fuel water separators.

=====

Al Warren Oil Co., Inc.
1646 Summer St
Hammond, IN 46320
800-327-8903
****WINTER BLEND****

Units : T65
Driver : (002) BETKIS, MIKE
BOL : '

Customer Arriv Time: 03/17/2020 13:35:00
Delivery Start Time:
Delivery Cmplt Time: 03/17/2020 14:10:00
=====

Sales Order: D0000589002

Ship To # : L09687
Ship To Address:
COLLEGE OF DUPAGE COMMUNITY SCHOOL
DISTRICT 502
425 FAWELL BLVD
GLEN ELLYN, IL 60137

Customer # : C08363
Customer Address:
COLLEGE OF DUPAGE COMMUNITY SCHOOL
DISTRICT 502
425 FAWELL BLVD
ACCTS PAYABLE
GLEN, IL 60137

=====

Product 1: #2 ULSD 15 ppm Sulfur On
Highway Diesel

Tank ID	Net	End Time
ULSD	300.0	14:10:00

Product 1 Delivered: 300.0

Product 2: Gasoline (87 Octane)

Tank ID	Net	End Time
87OCT	1800.0	14:10:00

Product 2 Delivered: 1800.0

=====

Total Delivered: 2100.0

=====

Lat: 41.96439 Lon: -87.941483

Information:

Drawer: Accounts Payable - Invoices
Vendor Number: 1504171
Vendor Name: Al Warren Oil Company, Inc.
Invoice Number: W1297933
Invoice Date: 03/19/20
PO Number: B0365251
Check Number: 0266562
Check Amount: \$ 2,813.97
Check Date: 04/14/2020
Department ID: 00701
Reviewer Name: Kathy Striplin
Voucher Number: V0608912
Redaction Type: None
Document Type: AP Invoice

Document Below

From: QRI@alwarrenoil.com
Sent: Thu Mar 19 14:35:03 CDT 2020
To: invoicing@cod.edu
CC:
Subject: Al Warren Oil Invoice

Attached is invoice #W1297933. Meter ticket(s) are also attached. We thank you for your business!

CONFIDENTIALITY NOTICE: This email message is intended only for the person or entity to which it is addressed and may contain confidential and/or privileged material. If you received this electronic transmission in error, please be aware that any unauthorized review; copying, use, disclosure or distribution of this information is prohibited. If you are not the intended recipient, please contact the sender by reply email, then delete the original message, including any attachments, and destroy all copies.

AL WARREN OIL CO., INC.

Since 1948

Specialized Petroleum Marketers

Sold To: COLLEGE OF DUPAGE COMMUNITY SCHOOL DISTRICT 502
ACCTS PAYABLE
425 FAWELL BLVD
GLEN ELLYN, IL 60137

Invoice #: W1297933
Invoice Total: \$2,310.12
Invoice Date: 03/19/20
Customer #: C08363

Ship To: COLLEGE OF DUPAGE COMMUNITY SCHOOL DISTRICT 502
425 FAWELL BLDV
GLEN ELLYN, IL 60137 DU PAGE

SO #: D0000589002
Purchase Order #: 352822

APPROVED

03/25/20 - BRUCE SCHMIEDL

Job #	Delivery Date	Quantity	Description	Unit Price / Rate	Job Total
1528482	03/17/20	1800.000	GAL ONCL 10% REG S/L ADDED 17 OCT	.8924	\$1,606.32
Document #: 157757					
State M.F. Tax				0.3800/Gal	684.00
IL U.S.T.				0.0030/Gal	5.40
IL E.I.F.				0.0080/Gal	14.40
Load Total:					\$2,310.12

Order taken by Corporate office.
Al Warren Oil Company, Inc., 1646 Summer St., Hammond, IN 46320

Delivery Location Total: \$2,310.12

INVOICE REVIEWED
OKAY TO PAY
KATHY STRIPLIN 03/20/20

ELECTRONIC PAYMENT PREFERRED

ACH/WIRE INSTRUCTIONS:

Fifth Third Bank
ABA: 071923909
Account: 1900002976
Beneficiary: AL Warren Oil Company Inc.
Email Remittance: awocbilling@alwarrenoil.com

REMIT:

AL Warren Oil Company Inc.
P.O. Box 2279
Hammond, IN 46323


INVOICE

TOTAL: \$2,310.12



1646 SUMMER STREET, HAMMOND, IN 46320
WWW.ALWARRENOIL.COM
AWOCBILLING@ALWARRENOIL.COM
Phone: 219.228.5050 Fax: 219.852.6010





WINTER FUEL PROGRAM

Dear Valued Customer,

With winter approaching we wanted to take this opportunity to notify you of our program for this upcoming season.

We will begin our winter additive blending process for all Diesel fuels on November 6th. We will cease biodiesel blending for above-ground tank deliveries (unless otherwise requested) and all direct-to-unit fills on December 2nd and proceed with distributing Ultra-Low Sulfur Diesel #2 with winter additive.

Please be advised that diesel fuel at the refinery level may contain up to 5% biodiesel without disclosure. Al Warren Oil Company, Inc. will not increase the percentage of biodiesel unless requested by customer.

In the anticipated occurrences that temperatures will reach single-digit and sub-zero range, it is Al Warren Oil Company, Inc.'s intent (based on product availability) to implement the following blending procedure for Ultra-Low Sulfur Diesel #2 and Ultra-Low Sulfur Diesel #1 including winter additive:

Less than 5°F	Less than -5°F	Less than -15°F
90% #2 — 10% #1 blend	80% #2 — 20% #1 blend	50% #2 — 50% #1 blend


****Do not over treat fuel with additional additives! AWOC's winter blends are treated with the maximum allowed concentration of additives. Over additizing by end user could have negative effects!**

Orders for exact gallons of "straight" Ultra-low Sulfur Diesel #1 tank fills may be satisfied upon request

Please be advised that pricing for the above blends and Ultra-low Sulfur Diesel #1 are subject to market conditions and possible transportation fees

ORDER NOW

Please contact your sales representative or dispatch (800-327-8903) for any requests or questions.
We thank you for your business and look forward to continuing service for all your needs.



FLEET MAINTENANCE

Al Warren Oil has products to help you through the winter.

BEFORE WINTER STARTS

- Have all vehicles winterized beginning November 01.
- Drain fuel water separators. (Constantly monitor and maintain above and beyond scheduled PM inspections)
- Change fuel filters (use highest OEM accepted micron fuel filters. Example 10-15 micron fuel filters as opposed to 2-5 micron fuel filters)
- Inspect fuel tanks for condensation
- Always top fuel tanks prior to equipment shut down
- Constantly monitor fuel system for condensation and microbial contamination

-35 PREMIUM WINDSHIELD DEICER

- Extreme cold calls for extreme fluid. Use our Negative 35 Premium Windshield Deicer for the harsh winter ahead. Ensure clear vision for your fleet.

Chevron XLC Antifreeze/Coolant 50/50

Delo® XLC Antifreeze/Coolant is a non-nitrated extended life OAT (Organic Additive Technology) formulation for heavy or light duty vehicles and other equipment. Delo XLC is formulated with an aliphatic carboxylate corrosion inhibitor system available as a concentrate and a premix 50/50.

CUSTOMER BENEFITS

Delo XLC Antifreeze/Coolant products deliver value through:

- Long Service Life — Service life of 1,000,000 miles / 1,600,000 km / 15,000 hours
- Excellent Protection — Excellent protection against pitting, corrosion and erosion even on hard to protect metals like aluminum.
- Hardware Life — Maximum water pump life due to no silicate formula.
- Compatibility — Compatible with conventional antifreeze.

12 TO 72 HOURS BEFORE EXPECTED TEMPS OF ZERO DEGREES OR COLDER

- Treat saddle tanks with fuel deicer - 1 qt per 50 gallons of diesel fuel
- Before shutting engine down, idle engine for 10-15 minutes to circulate treated fuel thru the entire fuel system.
- First start, let engine idle for 30-45 minutes. This will allow warm fuel to return fuel tanks and vital engine components. Thus dissolving any wax or ice build up in fuel. If adequate warm up time is not done, heavy waxy fuel will load up fuel system and engine will shut down due to fuel starvation.

WHAT DOES DIESEL EXHAUST FLUID DO?

- Diesel Exhaust Fluid is sprayed into the diesel exhaust streams of diesel engines to lower the concentration of nitrogen oxide, NOx, in emissions.

WHY BLUEDEF DIESEL EXHAUST FLUID?

- Engineered for use in Selective Catalytic Reduction (SCR) systems on diesel engines, BlueDEF diesel exhaust fluid is comprised of a high-purity synthetic urea and deionized water mixture that improves emissions and fuel economy.

HOW DIESEL EXHAUST FLUID WORKS.

- When injected into the exhaust stream with a specialized dosing module, BlueDEF's water vaporizes, leaving ammonia molecules en route to the catalytic converter; once there, it converts NOx molecules into harmless nitrogen and water vapor—making for cleaner emissions. To ensure Selective Catalytic Reduction (SCR) performance, diesel exhaust fluids must adhere to the ISO 22241 Standards.

BE PROACTIVE

Utilize engine block heaters. / Park trucks inside when possible. / Drain fuel water separators.

=====

Al Warren Oil Co., Inc.
1646 Summer St
Hammond, IN 46320
800-327-8903
****WINTER BLEND****

Units : T65
Driver : (002) BETKIS, MIKE
BOL : '

Customer Arriv Time: 03/17/2020 13:35:00
Delivery Start Time:
Delivery Cmplt Time: 03/17/2020 14:10:00
=====

Sales Order: D0000589002

Ship To # : L09687
Ship To Address:
COLLEGE OF DUPAGE COMMUNITY SCHOOL
DISTRICT 502
425 FAWELL BLVD
GLEN ELLYN, IL 60137

Customer # : C08363
Customer Address:
COLLEGE OF DUPAGE COMMUNITY SCHOOL
DISTRICT 502
425 FAWELL BLVD
ACCTS PAYABLE
GLEN, IL 60137

=====

Product 1: #2 ULSD 15 ppm Sulfur On
Highway Diesel

Tank ID	Net	End Time
ULSD	300.0	14:10:00

Product 1 Delivered: 300.0

Product 2: Gasoline (87 Octane)

Tank ID	Net	End Time
87OCT	1800.0	14:10:00

Product 2 Delivered: 1800.0

=====

Total Delivered: 2100.0
=====

Lat: 41.96439 Lon: -87.941483